



- 1080P HD camera 123-degree wide angle clear and fluid video picture
- Manually adjustable lens
- The lens can be adjusted up and down, supporting Angle and elevation shooting
- Fiber like LED status light and capacitive touch control panel for volume up, down and microphone mute
- High-tech 360-degree mic coverage 256ms acoustic echo cancellation Full duplex Dynamic Noise Reduction (DNR). Clear, unmixed and not harsh sound quality;
- No driver required, plug and play over USB cable.

# I-65

## HD Video Sound Pole

For use as a portable integrated conference system for desktops and tabletops

The I-65 is a digital conference pole integrated with HiFi audio and a wide-angle video camera. It is mainly used for small to middle size conference (huddle) rooms that seat up to 8 participants. It can be used for business, client meetings, job interviews, training, education, doctor-patient, tele-medicine, legal-practice, family, gaming and entertainment.

It is a USB network audio and videoconference speaker pole, it is compact, can be easily moved between rooms or taken on the road, it can be stored and connected to any type of PC or laptop.

It does not require a driver and supports either audio only or audio and video conferences utilizing online platforms such as Zoom, Skype, Microsoft Teams, Google Hangouts and Cisco Webex. It can also be used as an external microphone and HiFi speaker for your personal computer with amazing sound.

Equipped with 1080P HD camera on the I-65 provides users with a high-quality Internet video meetings, with a high definition real-time synchronized video and a sound pickup distance of 3 meters. The omnidirectional 360-degree microphone is used with strong anti-interference ability and wide range of sound pickup.

In the use of good broadband connection, the video image is clear, fluid and smooth and voice calls are natural. It has strong echo suppression and noise reduction abilities.

The I-65 requires no drivers and connects to a PC through a USB cable.

### Core Telesys Innotrik Europe Centers

For DACH (Germany, Austria, Switzerland)	DACH@innotrik.eu
For France	FR@innotrik.eu
For Spain and Portugal	ES-PT@innotrik.eu
For Italy	ITALIA@innotrik.eu
For UK and Ireland	UK-IE@innotrik.eu
For Nordics (DK, SE, NO, FI, IS)	NORDICS@innotrik.eu
For Central & Eastern Europe (Excluding Russia)	CEE@innotrik.eu

[www.innotrik.eu](http://www.innotrik.eu)

### Specifications

- System: Lens, Image Sensor, USB Interface controller, Noise-suppression and sidetone cancellation Audio
- Size: 62(L) x 62 (W) x 235(H) mm, 465g
- Color: Black
- Interface: USB 2.0
- Power: USB Cable (5V/500mA)
- Lens: 1 /2.8" Fixed Focus
- Angle: 120°
- Image Sensor: Full HD CMOS
- Microphone: Digital 100Hz-8000Hz Frequency Response with - 22dB@1kHz (0dB=1V/Pa)
- Loudspeaker: 10 steps up-to 94dBA Frequency response 300-22KHz
- Video: 1920x1080p
- Image transfer rate: Full HD CMOS
- Audio: DAP, Full Duplex, 256ms echo cancellation and 360° Pickup
- Object Distance: 30-300cm
- OS: Windows® 7,10 MAC OS 8.1+
- Certification: CE, FCC

### Order Detail

Model: I-65  
SKU: 00006972  
EAN: 4260618370018

