



I-1208

HD Video Camera with 1 Wireless Speakerphone For use as a video & audio conference system for small 4-6 person meetings

- Camera includes 2.4GHz radio for the communication and synchronization with the wireless speakerphone over a single USB Connection.
- 1080P video 120° shooting angle and 1080P clear and fluid image
- Mechanically adjustable lens. The lens can be adjusted vertically -30 to 30 degrees and horizontally -150 to 150 degrees, enabling flexible shooting angles
- High-Definition Audio Speakerphone with 360-degree MIC coverage, 256ms acoustic echo cancellation Full duplex Dynamic Noise Reduction (DNR)
- Easy operation with no need driver needed.
- Plug and Play with USB



The I-1208 is equipped with both a HD 1080P video camera and a high definition speakerphone. The camera has an impressive 120° wide shooting angle and includes a built-in 2.4GHz. TX/RX radio that communicates and synchronizes real-time audio and video with the wireless handsfree tabletop speakerphone.

It is suitable for small sized conference rooms with teams of 4-6 people in one conference. It is ideal for business, online training, webinars, remote job interviews for teams, education, tele-medicine, doctor-patient remote appointments and attorney-client meetings, family rooms and entertainment.

The I-1208 is compatible with common online conference platforms such as Zoom, Skype, Microsoft Teams, Google Hangouts, Cisco Webex and others.

A 1080P HD camera provides broadcast quality Internet video meetings with high definition synchronized fluid clear video image.

The 2.4GHz wireless speakerphone includes Echo Cancelling intelligent audio technology, enabling up to 3m pickup range with clear synchronized bi-directional audio

Core Telesys Innotrik European Centers:

For DACH (Germany, Austria, Switzerland)

For France

For Spain and Portugal

For Italy

For UK and Ireland

For Nordics (DK, SE, NO, FI, IS)

For Central & Eastern Europe (Excluding Russia)

DACH@innotrik.eu

FR@innotrik.eu

ES-PT@innotrik.eu

ITALIA@innotrik.eu

UK-IE@innotrik.eu

NORDICS@innotrik.eu

CEE@innotrik.eu

www.innotrik.eu

Specifications

- System: Lens, Image Sensor, USB Interface controller, 2.4GHz wireless processing unit, intelligent audio processing, indicators, Lithium Ion Battery for 7-10 hour operation.
- Sizes mm: Camera 104x 139x 124, Speakerphone 155 x 148 x 37
- Net Weight: Camera: 500g Speakerphone: 337g
- Interface: USB 2.0, 3.5 mm earphone
- Power: Camera: USB Cable (5V/500mA), Speakerphone: Lithium battery.
- Lens: 1/2.8" Fixed Focus
- Angle: 120°
- Image Sensor: Full HD CMOS
- Audio: 3-inch anti-magnetic speaker, omni-directional microphones 100-80000Hz sensitivity
- Video: 1920x1080 F-Numb. 2.0 30FPs
- Image transfer rate: 30FPsObject Distance: 30-300cm
- OS: Windows® 7,10 MAC OS 8.1+
- Certification: CE, FCC

Order Detail

Model: I-1208 SKU: 00006972

EAN: 4260618370018

