



I-1200S

Pro-HD Flip-Mount Conference Camera

For use as conference camera adding amazing video to your audio conference

- 1080P HD Camera with 120° wide range shooting angle
- Clear and smooth fluid video picture
- Mounting on ceiling or wall with gyro 180° image flip and alignment
- The lens can be adjusted vertical -30 to 30 degrees and horizontally -150 to 150 degrees, enabling flexible shooting angles in any room
- Network camera technology supporting web-based video meetings, such as Zoom, Skype, Microsoft Teams, Google Hangouts and others
- Easy operation. No driver needed, just plug USB and call
- Strong bezel clip is suitable for different screen sizes and thicknesses
- Wall or optional stand mountable

The I-1200HD camera equipped with 1080p broadcast technology and a 120° wide viewing range angle that is suitable for different size video conferences whether for business, client meetings, training, education, doctor-patient, tele-medicine, legal-practice, family, gaming and entertainment.

It can be mounted on walls or ceiling with image flipping technology using a gyro sensor. It is simple to operate and does not require the installation of a driver and works on Microsoft and Apple operating systems. It is compatible with common online video conference software, such as Zoom, Google Meet, Skype, Microsoft Teams, Cisco Webex and most all others.

The 1080P HD camera is specifically engineered for high quality Internet video meetings, with high definition real-time synchronization with clear flowing video images making video conferences feel real, giving users a high-quality experience.

Its design and style are beautiful and robust with a thin electrostatic powder metal housing with a fine feature red ring around the circumference of the external housing. The structure is compact and robust with an adjustable shooting angle. It can be placed anywhere over a monitor and is wall mountable. An available optional food stand is available.

Just plug the I-1200 to a PC via the included USB cable, select the input device on the PC and you are good to go.

Core Telesys Innotrik Europe Centers:

For DACH (Germany, Austria, Switzerland)	DACH@innotrik.eu
For France	FR@innotrik.eu
For Spain and Portugal	ES-PT@innotrik.eu
For Italy	ITALIA@innotrik.eu
For UK and Ireland	UK-IE@innotrik.eu
For Nordics (DK, SE, NO, FI, IS)	NORDICS@innotrik.eu
For Central & Eastern Europe (Excluding Russia)	CEE@innotrik.eu

www.innotrik.eu

Specifications

- System: Lens, Image Sensor, USB Interface controller, Gyro sensor, 180° Image to screen flip
- Size: 104 (L) x 139 (W) x 124 (H) mm
- Net Weight: 465g
- Color: Black
- Interface: USB 2.0
- Power: USB Cable (5V/500mA)
- Lens: 1/2.8" Fixed Focus
- Angle: 120°
- Image Sensor: Full HD CMOS
- Pitch motion: ~30°~30°
- Horizon motion: 150°~150°
- Video: 1920x1080p
- Image transfer rate: 30FPS
- F-Number: 2.0
- Object Distance: 30-300cm
- OS: Windows® 7, 10 MAC OS 8.1+
- Certification: CE, FCC

Order Detail

Model: I-1200S
SKU: 00006972
EAN: 4260618370018

